

### SCHULZ

# SCT 5000 FLEX HE

Air Compressors

The SCT 5000 Flex HE rotary-screw compressors are highly energy efficient, making them suitable for 24/7 operations. They offer higher performance, reduce energy consumption, and significantly lower costs.

Available in models from 3 to 100 hp and with 1 to 3 stages, these compressors feature a closed permanent magnet motor, oil-cooled, with IE-4 class efficiency (highest efficiency rating), and IP54 protection rating.

In other words, with protection against dust and water sprays, the SCT 5000 Flex HE rotary-screw compressors are excellent for environments exposed to dust clouds and moisture.

The product line also features a variablespeed frequency inverter that controls the motor's speed and torque according to the factory's air demand. This enables reducing pressure fluctuations in the system.

SCHULZ

Higher performance, lower energy consumption, and cost reduction.



Compressors suitable for 24/7 operation

Models from 3 to 100 hp From 1 to 3 stages



SCT **5006** FLEX HE SCT **5008** FLEX HE





SCT **5030** FLEX HE SCT **5050** FLEX HE



SCT **5100** FLEX HE



### **KEY APPLICATIONS:**

- Automotive industry
- Metalworking industry
- Textile industry
- Plastics industry
- Beverage industry
- Agro-industry



# IE4 EFFICIENCY MOTOR: THE HIGHEST CLASS OF ENERGY EFFICIENCY

Zero transmission loss — motor up to 10% more efficient compared to an induction motor with the same capacity



# SMART CONTROL PANEL WITH MAINTENANCE ALERTS

Easy operation enhances safety and extends the compressor's lifespan



### **HIGH-PRECISION OIL FILTER**

The high-efficiency filtration system ensures quality compressed air



### PERMANENT MAGNET MOTOR

With fewer components and high quality, it requires no preventive maintenance and offers great durability (it does not demagnetize)



## LOWER NOISE LEVEL (68 TO 74 DBA)

Greater acoustic comfort in work environments



# VARIABLE-SPEED FREQUENCY INVERTER

High stability, reliability, and significant reduction in energy consumption

MODEL	MOTOR POWER				DISPLACEMENT POWER	OPERATING PRESSURE	COMPRESSOR UNIT	TANK	TANK OUTLET TUBE	COMPRESSOR WEIGHT	DIMENSIONS (L x W x H)
	kW	HP	Hz	٧	cfm	bar	Stages	liter	Ø pol	kg	mm
SCT 5003 Flex HE	2,2	3	60	220	8	10	1	160	G3/4"	201,5	1095 x 540 x 1377
SCT 5006 Flex HE	4	5,5	60	220	16	10	1	160	G3/4"	201,5	1095 x 540 x 1377
SCT 5008 Flex HE	5,5	7,5	60	220	20	10	1	160	G3/4"	201,5	1095 x 540 x 1377
SCT 5010 Flex HE	7,5	10	60	220	32	10	1	260	G3/4"	296	1095 x 540 x 1377
SCT 5030 Flex HE	22	30	60	220	141	8	2	-	G1 1/4"	600	1100 x 900 x 1400
SCT 5050 Flex HE	37	50	60	220	250	8	2	-	G1 1/4"	650	1150 x 950 x 1400
SCT 5100 Flex HE	74	100	60	220	526	8	3	-	G2	2500	2670 x 1880 x 1820

# SCHULZ











### SCHULZ COMPRESSORES

Rua Dona Francisca, 6901 A - Distrito Industrial Fone: 47 3451.6000 - 89219-600 - Joinville - SC schulz@schulz.com.br

#### SCHULZ - SÃO PAULO

Av. Indianápolis, 1435 - Planalto Paulista Fone: 11 2161.1300 - 04063-002 - São Paulo - SP schulzsp@schulz.com.br



### SCHULZ OF AMERICA, INC.

3500, Lake City Industrial Court - Acworth, GA 30101 Phone # (770) 529.4731 - Fax # (770) 529.4733 sales@schulzamerica.com | www.schulzamerica.com



#### SCHULZ - CHINA

Building no. 3 (South) - No. 19, Zheng Lang Road FengXian District - Shanghai, China ZIP CODE: 201413





